

AUTOMATED SOFTWARE ROBOT GENERATOR

Priority Documents

This document claims priority to an earlier filed provisional patent application filed on November 1, 2002, having serial number 60/423,648.

Field of the Invention

This invention pertains to the field of computer programming. More specifically, the invention relates to a software program that can generate source code for other computer programs that can then robotically manipulate existing web sites. The software program may also trace, monitor and add support framework to an interactive internet browser. Moreover, an end user can modify the source code generated by the software to further increase the utility of the generated software source code.

BACKGROUND OF THE INVENTION

The internet, and more specifically, the World Wide Web, has hundreds of millions of pages available, waiting to present information on a variety of topics to an individual.

In addition, many companies, organizations, and individuals have constructed true applications using the World Wide Web as the delivery medium. Consumers can now conduct on-line banking, shop for automobiles, participate in on-line auctions, and many other activities of a transactional nature. World Wide Web based applications such as those mentioned above all present the user with the various screens and data that make up the application through a web browser such as Netscape Navigator, or Microsoft Internet Explorer. Software engineers term these types of World Wide Web transactional programs 'Web Applications' in contrast to software applications that run on older text based terminals, or in contrast to older client server technologies. Broadly then, World Wide Web has produced 2 classes of content. The first class of content may be read-only content, in which the user is directed to a specific web page and can then read the content of that page. The second class of content are Web applications, wherein the user actually enters data in an interactive manner to perform some tasks, like shopping for a product, performing a banking transaction, etc.

All World Wide Web applications and content present and retrieve user input using (broadly) two technologies. The first is the actual network protocol that is hidden from the user. This protocol is widely known as the Hypertext

Transfer Protocol, or simply 'HTTP'. The format of the information flowing over HTTP and subsequently accepted by a web browser, or conversely a web server is Hypertext Markup Language, or simply 'HTML'.

A very important part of web technology is that it functions over a public network. Thus almost anyone can, from a home computer, view web pages that are actually published all over the world. From a business perspective, the 'publicness' of the World Wide Web has removed a big barrier for moving data between companies and companies, and between companies and individuals. Heretofore, if two companies wanted to exchange business information, they would typically construct a private network, then agree on a protocol, then implement software that supported the agreed upon protocol, then transfer the data. Usually that process took months or years of work. Today, using the World Wide Web, each company simply publishes the data to their web server, and any of its authorized partners can see the data visually using a web browser.

As the web grew in the 1990's billions of web pages were produced. In addition, thousands of web applications were produced. While on the whole this has been a positive development for technologists, it has created a unique problem as regards integration of content and data from these many web pages and applications. Web technology today

focuses on human beings being able to interact with a web browser to view and modify web based information. However there is a great need for machine to machine communication over the Internet, as contrasted with human to machine which is what constitutes the bulk of all activity on the Internet today.

Machine to machine communication over the internet using HTTP and HTML is problematic. The fundamental reason for that is that HTML is more suitable as a publishing format, rather than a data exchange format. For example, it is trivial for a human to use a web browser to go to a banking site and check his/her account balance, it is much harder to write a piece of software that will, from a computer, access a bank web site, login, and query for an account balance, returning the data, not in HTML, but in a more 'machine friendly' format like the Extensible Markup Language (XML).

Programs that access web sites, that are normally accessed by human users sitting at a computer using a web browser, are call variously 'software robots', 'robots', 'software agents', 'agents', 'programs' or other. Programs that access web sites appear from a network and data presentation format, to the web site as an end user would. The web site or web application receives and sends information exactly as it would to a real human user, but

instead the information is received, processed, and responded to by a piece of software running on a computer somewhere on the Internet, rather than a live human user using a web browser. In these applications, the web site, or web application does not know it is communicating with anything other than a web browser, when in fact it is communicating with a piece of custom written software.

Today the majority if not all of these robotic applications are hand written by skilled software engineers. New web sites and applications are being created at a rate that is much more rapid than the ability of software engineers to write corresponding robotic applications. So in general web applications today immediately allow human users to perform some function, but do not support machine to machine communication.

No invention exists today that automatically generates software robots that can manipulate existing web sites and web applications. The net effect of the invention is a dramatic reduction in the amount of time necessary to implement machine to machine communications that utilize existing web sites and web applications.

Moreover, no application or program exists today that uses a system of monitoring and analyzing functions placed to a distinct web browser or other network based application to produce an extract of network transactions that can be manipulated by software to perform the desire operation automatically.

Further, no system of application exists for a program to emulate the transactions of the network based application and mimic the transactions in later access of the same network based applications or other relevant network abilities.

SUMMARY OF THE INVENTION

The present invention provides a system and a method for generating a computer program to automate the process of searching and or retrieving data from a particular data pool for introduction to a user, performing machine to machine communications, retrieving web content, or robotically driving a transaction that exists on a web application. More specifically, the present invention provides a program that robotically manipulates existing web sites using computer source codes that is generated all or in part by the computer program and/or software. The system may trace, monitor and analyze a browser or network application to produce transactions and manipulate the data retrieved to automatically access previously un-accessible data from a web site.

To this end, in an embodiment of the present invention, a system for manipulating existing websites is provided. The system has a computer software program to collect data on existing websites. The program has a tracing means for tracing an existing website when the website is being

accessed by third party users. The system also has a filtering means for filtering the collected data on existing websites. Moreover, the system may generate a source code and software robot that mimic a user using a web browser on the site.

In an embodiment, the system for manipulating existing websites has a tracing means wherein the tracing means uses an application programming interface wherein said interface intercepts application programming calls and records the parameters and data passed to the call.

In an embodiment, the system for manipulating existing websites has a tracing means wherein the tracing means collects data from internet protocol network events, including winsock, WinInet, shell, security, User, Active Directory, HTML and DOM application programming interfaces.

In an embodiment, the system for manipulating existing websites has a computer program wherein the computer program monitors data and events running on Microsoft Windows operating systems.

In an embodiment, the system for manipulating existing websites has a computer program wherein the computer program

monitors data and events running on a third party operating system.

In an embodiment, the system for manipulating existing websites has a filtering means wherein the filtering means allows for removal of redundant and useless information collected during the tracing. The system may facilitate removal of network management packets that are acknowledgements and retries. The system may facilitate collation of IP packets into single HTTP based messages and collation of HTTP messages into single records of content objects, including HTML, images, audio, and other HTTP content.

In an embodiment, the system for manipulating existing websites has a filtering means wherein the filtering means analysis the trace performed. The analysis may show an XML record for each content object in the order the content was received. Moreover, the analysis may show an XML record redirect records and added redirect information, XML record for cookie reads, XML record for cookie writes and XML record for user navigation events. Still further the analysis may show HTTP header information such as XML and

various other management information relating to the network and user event traces.

In an embodiment, the system for manipulating existing websites has the source code wherein the source code is generated by the computer program and further wherein said source code mimics what a user is doing during tracing and is generated by transforming XML to XSL.

In an embodiment, the system for manipulating existing websites has the source code wherein the source code is generated by the computer program and further wherein said source code is generated by hard coding and further wherein said source code is generated by using a computer language to parse filtering means and generate some other useful product from the filtering means.

In an embodiment, the system for manipulating existing websites has the source code wherein the source code is transformed to XSL wherein a XSL code exists for popular languages including Java, JavaScript, Visual Basic, Cold Fusion, C/C++, Pascal and a plurality of other computer languages.

In an embodiment, the system for manipulating existing websites has a software robot wherein said software robot can interface with a website and manipulate the website during use.

In an embodiment of the present invention, a method for manipulating an existing website is provided. The method has the steps of: providing a computer software program to collect data on existing websites; tracing an existing website when the website is being accessed by third party users; filtering the collected data on existing websites; analyzing the data collected from traced and filtered websites; and generating a source code.

In an embodiment, the method further comprises the step of providing an application programming interface to record data from existing websites.

In an embodiment, the method further comprises the step of tracing an existing website to collect data from internet protocol events and a plurality of application programming interfaces.

In an embodiment, the method further comprises the step of allowing an end user to hard code the generated source code.

In an embodiment, the method further comprises the step of automating the generation of source code to an end user.

In an embodiment, the method further comprises the step of allowing the computer program to interface with an existing website to automatically produce a desired outcome including: automatic form fill-in on a web page; interfacing with a website to obtain information previously unattainable; performing system testing of a website; and performing software change controls to monitor existing websites for change to the underlying site.

In an embodiment, the method further comprises the step of integrating the software into a web browser as a browser plug-in.

In an embodiment, the method further comprises the step of integrating the software into a web browser as an extension wherein the integrated software may display debug messages, HTTP header parameters, and other data.

In an embodiment, the method further comprises the step of allowing an end user to click on a button in a web browser plug-in that completes multiple forms without further user intervention.

It is, therefore, an advantage of the present invention to provide an automated software robot generator and a method for using the same.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software can trace a browser and/or other network based application.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may monitor a browser and/or other network based application.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may filter a browser and/or other network based application.

Still another advantage of the present invention is to provide an automated software robot generator and a method

for using the same wherein the software may analyze a browser and/or network based application.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor, filter and/or analyze a browser and/or network based application to produce an XML representation of network transactions.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor, filter and/or analyze a browser and/or network based application to produce screen data manipulation techniques.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor, filter and/or analyze a browser and/or network based application to retrieve cookie activities.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor,

filter and/or analyze a browser and/or network based application to retrieve HTTP headers.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor, filter and/or analyze a browser and/or network based application to retrieve relevant network, user and/or other events.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor, filter and/or analyze Microsoft Windows based applications and being capable of attaching into the network event layer of the application and tracing it.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor, filter and/or analyze a Unix or Unix variant shared library and be capable of attaching into the network event layer of the unix application and tracing it.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may trace, monitor, filter and/or analyze a plurality of network applications and be capable of attaching into the plurality of network applications and tracing them.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may generate computer source code capable of emulating the transactions obtained from monitoring and filtering of network applications.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may generate computer source code capable of emulating the data, and other events obtained from monitoring and filtering of network applications.

An advantage of the present invention is to provide an automated software robot generator and a method for using

the same wherein the source codes generated by the software may be modified by an end user.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the source codes generated by the software may be modified by an end user to produce a large number of variations of output source codes.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may transform XML code into another source code language.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may use XSL to transform XML code into another source code language.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may use XSL to transform codes derived from the filtering and analyzed network trace into a source code language.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may modify a source code language to include support for an interactive browser.

An advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may modify a source code to include a playback function.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may modify a source code to include a debug function.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may employ a plug-in that may be inserted into browser application that may robotically drive the website.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may employ a plug-in that may be inserted into the browser application and that

may drive the website while displaying in the web browser the web pages that are being driven.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may employ a plug-in that may be inserted into a browser application and that may drive the website without showing the end user the web pages that are being driven.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may capture protocol and application data flowing over a network application.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may analyze a network trace and process that trace into an XML based code format.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may analyze the data

wherein packets of data that may have been in temporal order may be grouped into integrated blocks of data.

An advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may allow drag and drop or other manipulation of the XML extract in preparation for code generation.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify XML code using XSL.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify the XML code into XML.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify the XML code into computer source code.

Still another advantage of the present invention is to provide an automated software robot generator and a method

for using the same wherein the software may convert and/or modify the XML code into database records.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify the XML code into Microsoft Office documents.

An advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify the XML code into HTML or other internet formats.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify the XML code into Java and/or JavaScript.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify the XML code into Cold Fusion.

Another advantage of the present invention is to provide an automated software robot generator and a method

for using the same wherein the software may convert and/or modify the XML code into C++.

An advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may convert and/or modify the XML code into other source codes.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may be integrated into a browser as a browser plug-in or extension.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may be integrated into a browser and allow for stepping through the source code generated on a page by page or event by event basis.

Still another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein a web browser plugin is used to provide full interactive debugging capability to the software code that is generated during the tracing and code generation phases.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein a web browser plug provides the ability to do most common debugging functions on the generated source code, while viewing the affect of the source code statements in the web browser itself.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein debugging functions include single stepping the source code, inspecting variables, and setting debugging breakpoints.

Another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may allow for display of debug messages.

Yet another advantage of the present invention is to provide an automated software robot generator and a method for using the same wherein the software may allow for display of HTTP header parameters and/or other data in the plug-in.

DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic of the automated software robot generator system in an embodiment of the present invention;

Figure 2 is another schematic of the automated software robot system in an embodiment of the present invention;

Figure 3 is another schematic of the automated software robot system in an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Turning now to the drawings wherein elements are identified with numbers and like elements are identified with like numbers throughout the schematics, in an embodiment of the present invention, the program may perform a plurality of functions with respect to the tracing and monitoring, filtering and analyzing of the network data. For example, the computer software program may intercept network calls from a MS Windows application. The software may trace the network activity for the application as it observes the application in process. Typically, the network

activity involves the HTTP protocol, but in other embodiments may involve other IP and non-IP based protocols.

Figure 1 illustrates a screen capture of one embodiment of the present invention. In Figure 1, the program 1 may capture protocol and application data flowing over the network between the application being traced and one or more computers on a network attached directly or indirectly to the computer running the AFT software. The program 1 may use a tracing means 3 to monitor the flow of web traffic on the internet (not shown). The data from the network tracing means 3 may be visible to the operator, however, the traced data may also be completely hidden from view of the end user (not shown). The tracing means 3 may produce data that may be analyzed by an analyzing means 5 and processed into an XML based format 9. Data obtained after the analyzing means 5 may be converted 11 into XSL based format 13. Alternatively, the data may be converted into XSLT format 15. In an embodiment of the present invention, during the analysis phase 5, packets that were in temporal order are grouped into integrated blocks of data for send/receive transactions.

In another embodiment of the present invention, the program may allow for drag and drop or other manipulation of the XML extract 9 in preparation for code generation. Operations on the XML include, but are not limited to: adding XML nodes (not shown), deleting XML nodes (not shown), search and replace operations on nodes and data in the XML nodes (not shown).

The core data from which an embodiment of the present invention functions may includes data and events obtainable on a computer running the Microsoft Windows operating system in any of its incarnations including but not limited to Windows, Windows 95, Windows NT, Windows XP, hereinafter referred to as Windows.

The program may obtain data from a Microsoft or any third party supplied software by using an Application Programming interface (API) or software 'hook'. A software hook may work by intercepting Application Programming interface calls, analyzing and possibly recording the parameters and data passed to the API call as shown in Figure 2. The software may then pass the parameters and data onto the original target of the API call, namely the

Microsoft or third party library. In an embodiment of the present invention, the software may work by obtaining a detailed trace of various API calls and the parameters and data sent to and from those API's. The trace data may be saved in memory (RAM) or on a disk (see Figure 2).

In addition to the original raw trace data, an embodiment of the present invention may insert markers or tags in the trace that provide added information about events and data. The markers or tags may include timing, and other information used by an embodiment in the analysis and other phases.

As further illustrated in Figure 1, a hardware or software based network analyzer and/or analyzing means 5 may be used to facilitate and aid the tracing means 3 in tracing the network and provide a suitable network trace.

The software hook in an embodiment of the present invention traces a web browser such as Internet Explorer 55, or Netscape Navigator 57. However, the program may be used to trace non-browser applications such as e-mail clients 59, IP based file servers and many other types of non-browser applications. The data obtained from a browser and third

party supplied products may include, but is not limited to : Internet Protocol network event data 61 including data obtainable from the Windows socket or Winsock API; Data and events obtainable from the MS WinInet API; data and events obtainable from the MS shell API; data and events obtainable from the MS security API; data and events obtainable from the MS User API; data and events obtainable from the MS Active Directory API; data and events obtainable from MS HTML API; and data and events obtainable from MS DOM API.

Figure 2 also illustrates the tracing portion of the design of the software in an embodiment of the present invention. The tracing phase 5 may obtain a large amount of data during operation. A lot of the data obtained may be redundant in nature and not particularly useful in further processing, and further may be of little interest to the end user. To eliminate the redundancy of the filtered data, the software may analyze and /or remove 25 network management packets that are acknowledgements, retries, etc. Moreover, the software may collate the IP packets into a single HTTP based message and/or the software may further collage the HTTP messages into single records of content objects (not

shown). The objects may be HTML, images, audio, or other HTTP content. The HTTP may also include web pages, audio, video and or multiple other records. Additionally, HTTP interleaves content from multiple requests. In the initial analysis phase, an embodiment, re-collates the individual sent/received packets of a content object into a single content record.

Again referring to Figure 1, once the trace 3 is filtered 4, an analysis 5 of the filtered trace data may be preformed. The output of the initial analysis is XML 9. The XML 9 is referred to as the 'Extract', since it may contain a condensed version of the relevant trace events. In an embodiment of the present invention, the analysis phase may emit an XML record for each content object in the order that it was received. Moreover, the analysis phase may emit an XML record redirect and added redirect information; emit an XML record for cookie reads/writes; emit an XML record for user navigate events which may allow a user to click on a link on a browser; emit HTTP header information as XML; and may emit various other management information relating to the network and user event trace as needed.

One embodiment of the invention may produce source code 31 that may mimic what the user did during the recording and tracing phase. The source code 31 may be used on a client machine or on a server machine. Generations of source code 31 may be via an XSL transform of the Extract XML. Another embodiment for generating source code or other useful expressions of the extract may be by modification of the source code 33 that may be performed in other ways including hard coding or using a computer language to parse the extract and generate some other useful product from the extract.

In an embodiment of the present invention, the XSL exists for various popular languages including Java, JavaScript, Visual Basic, Cold Fusion, C/C++, Pascal and many others.

In an embodiment, parts of the AFT application may be integrated 35 into a browser as a browser plug-in or extension. In an embodiment, browser mode may allow interactive stepping through the source code generated on a page by page basis. In the alternative, the browser mode may allow interactive stepping through the source code generate

on a event by event basis. In Browser mode, embodiments may allow the program 1 to debug 37 the browser by displaying debug messages, HTTP header parameters, or other data in the plug-in.

Additionally, the technology may be used to perform automated page completion. In the preferred embodiment of the present invention, end-users tend to be concerned with filling in form information on multiple pages on a web site. An embodiment of the invention may allow the end user to simply click on the next or similar button in the plug in or on the actual web page, and the software sends the appropriate data over the network as if the user had actually typed in the values on the form.

In another embodiment of the present invention, a user may click on a "run" button in the plug-in that completes multiple forms without further user intervention.

Figure 3 illustrates the relationship of various software modules in an embodiment. The software modules may be divided into those that run during the analysis data capture phase, and software that may run either on a client and/or on a server machine during playback of generated

code. Client playback may be either via a dedicated win32 application, or a web browser plug in and/or browser helper object. As Figure 3 illustrates, the Graphic user interface 39 manages the main application, windows, and controls necessary to trace, analyze, generate source code and test. The GUI support 41 provides high level support routines for manipulating the extract, trace and other high level objects. The Internet Explorer (or any other browser application) DOM Hook 43, hooks the document model, manipulates and controls the record/playback, browser windows, winsock.dll, wininet.dll, user32.dll and others. The Hooking DLL 45 hooks winsock.dll, wininet.dll, user32.dll and others.

The program also includes base utilities 47 and server playback modules that may have code for thread, lock, process, and other core operating system and software functions. The program may also have a fully single threaded version of the server software.